

### 5MP bullet IP camera DWC-MB95Wi28TW/ DWC-MB95Wi36TW





















2.8, 3.6mm Fixed Lens Options

**WDR** 

Smart IR'

Warranty

## Summary

These MEGApix® IP cameras are NDAA compliant and deliver crystalclear images at 5MP resolution and real-time 30fps. The bullet camera features 2.8mm and 3.6mm fixed lens options in an IP67rated, IK10 impact-resistant housing. Added intelligence includes line crossing, perimeter intrusion, video tampering detection and object classification. All MEGApix cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

#### Features

- 5MP 1/2.7" image sensor at real-time 30fps
- 2.8mm fixed lens (DWC-MB95Wi28TW)
- 3.6mm fixed lens (DWC-MB95Wi36TW)
- True Wide Dynamic Range (WDR)
- Multiple codecs (H.265, H.264, MJPEG) with simultaneous dualstream
- 164ft range Smart IR™
- Object classification video analytics
- Line crossing video analytics
- Perimeter intrusion video analytics
- Video tampering with scene change detection video analytics
- Video tampering with video blur detection video analytics
- Video tampering with abnormal color detection video analytics
- Smart DNR™ 3D digital noise reduction
- True day/night with mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Backlight compensation (BLC)
- De-Fog™ extreme weather image compensation
- Auto white balance (AWB)
- Motion detection
- Audio input
- Micro SD/SDHC/SDXC class 10 card slot (card not included)
- Web server built-in
- PoE Class 3 and DC12V
- ONVIF conformant, profile S
- NDAA compliant
- IP67 dust-tight and waterproof to 3 feet
- 5 year warranty



#### Mounting accessories (Optional)







Increase sales and profitability. Sign up and become a DW Channel Partner today!











# **Specifications**

MODELS IMAGE	DWC-MB95Wi28TW	DWC-MB95Wi36TW	
Image sensor	5MP 1/2.7" CMOS		
Total pixels		x 1944 (V)	
·	0.02 lux (color)		
Minimum scene illumination	0.0 lux (B/W)		
S/N ratio	50dB		
LENS			
Focal length	2.8mm, F1.6	3.6mm, F1.6	
Lens type		d lens	
Field of view (FoV)	98.5°	81.4°	
IR distance		range	
1/0	15 110	14.150	
Audio in / out	1 audi	o input	
Audio compression		A/U	
OPERATIONAL		, .	
Shutter mode	Auto, manual		
Shutter speed		/10000s	
Auto gain control		Auto	
Day / night	Auto, day (color), night (B/W), schedule		
Smart DNR™ 3D digital noise	3D DNR		
reduction			
Wide dynamic range (WDR)	True WDR low, middle, high		
Wide dynamic range (WDR) dB	120dB		
Privacy zone	4 programmable privacy masks		
Camera analytics	Line crossing, perimeter intrusion, video tampering detectic (scene change, video blur, abnormal color detection), obje- classification (differentiate humans from objects)		
Backlight compensation (BLC)	Yes		
De-Fog	Yes		
Mirror and flip	Yes		
Alarm notifications	Notifications via email or FTP server		
Memory slot	Micro SD/SDHC/SDXC card up to 256GB (not Included)		
NETWORK			
LAN		nce 10/100 LAN	
Video compression type	H.265, H.264, MJPEG		
Resolution	5MP, 4MP, 2K, 3MP, 2.1MP/1080P, 720P (60Hz: 1 - 30fps; 50Hz: 1-25fps) HFR mode: 1080P / 720P (60Hz: 1 - 60fps; 50Hz: 1-50fps		
Frame rate	Up to 30fps a	t all resolutions	
Video bitrate	64 Kbps ~ 8 Mbps		
Bitrate control	Multi-streaming CBR/VBR at H.264/ H.265 (controllable frame rate and bandwidth)		
Streaming capability		nt rates and resolutions	
IP		, IPv6	
Protocol	UDP, IPV4, IPV6, DHCP, NTP, RTSP, RTP, RTCP, ICMP, IGM PPP0E, DDNS, SMTP, FTP, SNMP,HTTP, 802.1x, UPnP, HTTP QoS		
Security	IP filtering, MAC filtering, aut		
ONVIF conformance		es	
Mohariouer	OS: Windows*		
VVEU VIEWER			
Web viewer		ernet Explorer	
Video management software		ernet Explorer rum* IPVMS	
Video management software ENVIRONMENTAL	DW Specti	rum* IPVMS	
Video management software ENVIRONMENTAL Operating temperature	DW Specti -22°F ~ 140°F	rum* IPVMS (-30°C ~ 60°C)	
Video management software ENVIRONMENTAL Operating temperature Operating humidity	DW Specti -22°F ~ 140°F 95% RH (non	rum* IPVMS (-30°C ~ 60°C) I-condensing)	
Video management software ENVIRONMENTAL Operating temperature Operating humidity IP rating	-22°F ~ 140°F 95% RH (nor IP67	rum* IPVMS (-30°C - 60°C) I-condensing) -rated	
Video management software ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications	DW Specti -22°F ~ 140°F 95% RH (nor IP67- FCC, CE, RG	rum* IPVMS  (-30°C - 60°C) condensing) -rated  DHS, ONVIF	
Video management software ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications	-22°F ~ 140°F 95% RH (nor IP67	rum* IPVMS  (-30°C - 60°C) condensing) -rated  DHS, ONVIF	
Video management software ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications ELECTRICAL	DW Specti -22°F - 140°F 95% RH (nor IP67- FCC, CE, RC DC 12V, POE IEEE 802.3af CI	rum* IPVMS  (-30°C - 60°C) condensing) -rated  DHS, ONVIF	
Video management software ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications ELECTRICAL Power requirement Power consumption	DW Specti -22°F - 140°F 95% RH (nor IP67- FCC, CE, RC DC 12V, POE IEEE 802.3af CI	rum* IPVMS  (-30°C - 60°C) I-condensing) I-rated DHS, ONVIF  ass 3. (Adapter not included	
Video management software ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications ELECTRICAL Power requirement	DW Spectr -22°F - 140°F 95% RH (nor 1P67- FCC, CE, RI DC 12V, PoE IEEE 802.3af CI	rum* IPVMS  (-30°C - 60°C) I-condensing) I-rated DHS, ONVIF  ass 3. (Adapter not included	
Video management software ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications ELECTRICAL Power requirement Power consumption MECHANICAL	DW Specti -22°F - 140°F 95% RH (non IP67: FCC, CE, Rt DC 12V, PoE IEEE 802.3af CI 9	rum* IPVMS  (-30°C ~ 60°C)  I-condensing)  rated  OHS, ONVIF  ass 3. (Adapter not included	
Video management software ENVIRONMENTAL Operating temperature Operating humidity IP rating Other certifications ELECTRICAL Power requirement Power consumption MECHANICAL Material	DW Specti -22°F - 140°F 95% RH (nor IP67- FCC, CE, RI DC 12V, PoE IEEE 802.3af CI 9 Metal bull 8.69" x 3.16" x 2.77" (2	rum* IPVMS  (-30°C - 60°C)  -condensing)  -rated  OHS, ONVIF  ass 3. (Adapter not included  W  et housing	



