


#### 4MP vari-focal lens bullet IP camera DWC-VSBD04Mi





### Dimensions





8.69" (220.8mm

## Specifications

IMAGE	
Image sensor	4MP 1/3" CMOS
Total pixels	2560 x 1440
N distinguises and a sill succession of the second	0.005 lux (color)
Minimum scene illumination	0.0 lux (B/W)
S/N ratio	50dB
LENS	
Focal length	2.8 ~ 12mm, F1.4
Lens type	Vari-focal lens with motorized zoom and auto-focus
Horizontal Field of View	92°~31°
Vertical Field of View	48° ~ 17.2°
IR distance	164ft range
1/0	I lo fit fullige
Audio in / out	1 audio input and 1 microphone built-in
Audio compression	G.711A / U
OPERATIONAL	0.711A7 0
Shutter mode	Auto manual
	Auto, manual
Shutter speed	1/2s ~ 1/100000s
Auto gain control	Auto
Day / night	Auto, day (color), night (B/W), schedule Smart DNR™ 3D digital noise reduction
3D DNR	
Wide dynamic range (WDR)	True WD, 120dB
Privacy zone	8 programmable privacy masks
Video analytics	Line crossing, perimeter intrusion, video tampering
	detection (scene change, video blur, abnormal color)
Backlight compensation (BLC)	Yes
Mirror and flip	Yes
Alarm notifications	Notifications via email or FTP server
Memory slot	Micro SD, SDHC, SDXC up to 256GB (card not Included)
NETWORK	
LAN	802.3 compliance 10/100 LAN
Video compression type	H.265, H.264, MJPEG
Resolution	4MP, 3MP,2.1MP/1080P, 720P, D1, 480x240, CIF (60Hz: 1 ~ 30fps; 50Hz: 1~25fps)
Frame rate	Up to 30fps at all resolutions
Video bitrate	64 Kbps ~ 8 Mbps
Bitrate control	Multi-streaming CBR/VBR at H.264/ H.265 (controllable frame rate and bandwidth)
Church and in an annual sility a	Dual-stream at different rates and resolutions
Streaming capability	Maximum three (3) connections/streams at a time
IP	IPv4, IPv6
	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP,
Protocol	IGMP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x,
	UPnP, HTTPs, QoS
Security	IP filtering, MAC filtering, authentication (ID/PW), SSL/TSL
ONVIF conformance	Yes
	OS: Windows®, Mac® OS, Linux®
Web viewer	Browser: MS Edge, IE, Chrome, Firefox
Video management software	DW Spectrum <sup>®</sup> IPVMS
ENVIRONMENTAL	
Operating temperature	-22°F ~ 140°F (-30°C ~ 60°C)
Operating humidity	0-95% RH (non-condensing)
IP rating	IP67-rated
Other certifications	FCC, CE, ROHS, ONVIF, NDAA
ELECTRICAL	T CC, CL, ROHS, ONVIF, NDAA
	DC 12)/ DoE (Adapter pet included)
Power requirement	DC 12V, PoE (Adapter not included)
Power consumption	<8W
MECHANICAL	
Material	Metal bullet housing
Dimensions	8.69" x 3.16" x 2.77" (220.8 x 80.5 x70.6 mm)
Weight Warranty	1.52 lb (0.69 kg) 5 year warranty

www.digital-watchdog.com

# Summary

These MEGApix<sup>®</sup> IP cameras are NDAA compliant and deliver crystal-clear images at 4MP resolution and real-time 30fps. The bullet camera features a 2.8-12mm vari-focal lens in an IP67rated, IK10 impact-resistant housing. Added intelligence includes line crossing, perimeter intrusion and video tampering detection. All MEGApix cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

### Features

- 4MP 1/3" image sensor at real-time 30fps
- Vari-focal lens with motorized zoom and autofocus for complete remote lens control and focused image any time
- True Wide Dynamic Range (WDR) for clear images in challenging light
- Simultaneous streaming and multiple codec options for smart bandwidth management
- 164' Smart IR™ with intelligent camera sync for clear B/W images with no need for external light
- Line crossing video analytics
- Perimeter intrusion video analytics
- Video tampering with scene-change, video-blur and abnormal color detection video analytics
- Smart DNR<sup>™</sup> 3D digital noise reduction reduces noise and ghosting for motion in low-light environments.
- Privacy zones cover sensitive areas in the camera's field of view.
- Backlight compensation (BLC)
- Built-in microphone and audio input for direct communication between the monitoring station and the camera's location
- Local SD card slot for local recording in case of network loss
- Web server built-in for easy camera management from any browser
- PoE and DC12V for single cable simplified installation
- NDAA compliant for federal and government projects
- IP67-rated camera housing built to last
- 5 year warranty

#### Mounting accessories (Optional)



DWC-MBTJUNCW Junction box



Built for Users.



866.446.3595