


4MP fixed lens turret IP camera DWC-VSTB04Bi/DWC-VSTB04BiB





Dimensions

Unit: Inch (mm)



Summary

These MEGApix® IP cameras are NDAA compliant and deliver crystal-clear images at 4MP resolution and real-time 30fps. The IP67-rated turret camera features a 2.8mm fixed lens and a 360° camera gimbal for absolute view adjustment. Added intelligence includes line crossing, perimeter intrusion and video tampering detection. All MEGApix cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 4MP 1/3" image sensor at real-time 30fps
- 2.8mm fixed lens
- True Wide Dynamic Range (WDR) for clear images in challenging light
- Simultaneous streaming and multiple codec options for smart bandwidth management
- 100' Smart IR™ with intelligent camera sync for clear B/W images with no need for external light
- · Line crossing video analytics
- Perimeter intrusion video analytics
- Video tampering with scene-change, video-blur and abnormal color detection video analytics.
- White and black housing options available
- Smart DNR™ 3D digital noise reduction reduces noise and ghosting for motion in low-light environments.
- Privacy zones cover sensitive areas in the camera's field of view.
- Backlight compensation (BLC)
- Two-way audio with a built-in microphone for direct communication between the monitoring station and the camera's location.
- Local SD card slot for local recording in case of network loss
- Web server built-in for easy camera management from any browser
- $\bullet\,$ PoE and DC12V for single cable simplified installation
- NDAA compliant for federal and government projects
- IP67- and IK10-rated camera housing built to last
- 5 year warranty

Mounting accessories (Optional)





DWC-MT9JUNC White junction box





Specifications



IMAGE	
Image sensor	4MP 1/3" CMOS
Total pixels	2560 x 1440
•	0.005 lux (color)
Minimum scene illumination	0.0 lux (B/W)
C/NI ratio	
S/N ratio	50dB
LENS	0.0
Focal length	2.8mm, F1.6
Lens type	Fixed lens
Horizontal Field of View	94°
Vertical Field of View	50°
IR distance	100ft range
I/O	
Audio in / out	1 audio input and 1 microphone built-in
Audio compression	G.711A / Ú
OPERATIONAL	,
Shutter mode	Auto, manual
Shutter speed	1/2s ~ 1/100000s
Auto gain control	Auto
Day / night 3D DNR	Auto, day (color), night (B/W), schedule Smart DNR™ 3D digital noise reduction
	True WDD 120dB
Wide dynamic range (WDR)	
Privacy zone	8 programmable privacy masks
Video analytics	Line crossing, perimeter intrusion, video tampering
	detection (scene change, video blur, abnormal color)
Backlight compensation	Yes
(BLC)	res
Mirror and flip	Yes
Alarm notifications	Notifications via email or FTP server
Memory slot	Micro SD, SDHC, SDXC up to 256GB (card not Included)
NETWORK	Thick obb, abite, abite up to 2300b (card not included)
LAN	802.3 compliance 10/100 LAN
	H.265, H.264, MJPEG
Video compression type	10.200, 0.204, MIDREU
Resolution	4MP, 3MP,2.1MP/1080P, 720P, D1, 480x240, CIF
	(60Hz: 1 ~ 30fps; 50Hz: 1~25fps)
Frame rate	Up to 30fps at all resolutions
Video bitrate	64 Kbps ~ 8 Mbps
Dituata control	Multi-streaming CBR/VBR at H.264/ H.265
Bitrate control	(controllable frame rate and bandwidth)
	Dual-stream at different rates and resolutions.
Streaming capability	Maximum three (3) connections/streams at a time
IP .	IPv4, IPv6
IF	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP,
D	
Protocol	IGMP, PPPoE, DDNS, SMTP, FTP, SNMP,HTTP, 802.1x,
	UPnP, HTTPs, QoS
Security	IP filtering, MAC filtering, authentication (ID/PW), SSL/TSL
ONVIF conformance	Yes
	OS: Windows®, Mac® OS, Linux®
Web viewer	Browser: Microsoft Edge, IE, Google Chrome, Mozilla
	Firefox
Video management	FILETOX
Video management	DW Spectrum® IPVMS
software	Direction in the
ENVIRONMENTAL	
Operating temperature	-22°F ~ 140°F (-30°C ~ 60°C)
Operating humidity	0-95% RH (non-condensing)
IP rating	IP67-rated
IK rating	IK10 impact-resistant
Other certifications	FCC, CE, ROHS, ONVIF, NDAA
ELECTRICAL	I CC, CL, NOTIO, ONVII , NDAA
	DC 12V, PoE (Adapter not included)
Power requirement	
Power consumption	<5W
MECHANICAL	
Material	Metal turret housing
Housing color	DWC-VSTB04Bi: white
i lodali ig coloi	DWC-VSTB04BiB: black
Dimensions	4.25" x 3.77" (108 x 96 mm)
	1.01 lb (0.46 kg)
Weight	
Weight Warranty	5 year warranty













